Image & Image Set Metadata Fields

Below are two sets of metadata which will be stored in the new archive in regard to Images and the Image Sets to which they belong. Included where relevant are the equivalent fields in the Virtual Observatory ObsCore Data Model, a potential source from which to obtain the data, and a comment. The images table was written specifically with the idea of spatial images in mind. Other data products (spectra, time series, etc) would have different amounts of granularity in the header information available.

Images Database Table:

Column Name	Units	VO Equivalent	Source	Comments	
sourcename		target_name	OBJECT Keyword		
ra	deg	s_ra	Center of Ra Axis		
dec	deg	s_dec	Center of Dec Axis		
image_field _of_view	deg	s_fov	Quadratic Mean of the ra & dec extents (NAXISn*CDELTn)		
spatial_regi on		s_region	Derived from spatial Data	STC-S String Defined in the TAP (Dowler, et al 2010)	
a_element _count		s_xel1	Relevant NAXISn Keyword		
a_pixel_size			abs(Relevant CDELTn)		
dec_eleme nt_count		s_xel2	Relevant NAXISn Keyword		
dec_pixel_s ze			abs(Relevant CDELTn)		
spatial_res olution	arcsec	s_resolution	sqrt(BMAJ*BMIN)	Geometric mean of the synthesized beam axes.	
beam_axis _ratio			BMAJ/BMIN	Ratio of the synthesized beam axes.	
starttime	MJD	t_min		These values should be obtained by some larger-scale process. VlassMgr, in the case of	
endtime	MJD	t_max		quicklook images.	
exposure_ti me	s	t_exptime			
min_freque ncy	Hz	em_min	Minimum of Spectral Axis		
max_freque	Hz	em_max	Maximum of Spectral Axis		
rest_freque ncy	Hz		RESTFRQ Keyword	Used for transformations	
band_code			weblog	Requires outside information source for accuracy.	
polarization _id		pol_states	Polarization CRVALn value	CASA uses the CRVALn value to convey polarization information, with [1,2,3,4] mapped to [I,Q,U, V].	
				Default to 'None' in case of other values.	
elescope		instrument_na me	TELESCOP Keyword	This must accommodate images for multiple instruments (i.e. VLA + Single Dish)	
file_id			automatically generated	link to information about the physical file	
image_id		obs_id	automatically generated	Unique Identifier for the Image	
image_units		o_ucd	BTYPE & BUNIT Keywords	Description of the physical quantity measured in the image	
max_intens ity	image_ units		image table values		
min_intensi	image_ units		image table values		
rms_noise	image_ units		weblog	Both of these will need to come from the last stage of the imaging process, to maintain accuracy. For quicklook images, that is stage7. That may change (and will likely be different for the Single Epoch products).	

thumbnail		weblog, find the matching thumbnail image generated.	
tags			Internal tagging system to facilitate searches.
ra_pixel_size		Appropriate CDELTn	
dec_pixel_s ize		Appropriate CDELTn	

FITS Data Description Keywords:

For the purpose of generality, FITS provides a detail-independent method of data access. It's easier to think of the data axis descriptors in groupings by their axis number. The NAXIS keyword provides the total number of dimensions within the data. For the nth dimension of the data, we have a set of descriptor keywords which should be considered and used together:

· NAXISn - Total data size along this axis

CRPIXn - Our reference location

• CRVALn - The physical value at our reference location

. CDELTn - The increment along the axis

• CTYPEn - The axis label

• CUNITn - The axis units

The CTYPEn and CUNITn values provide information about the axis to which this group of values applies. The rest of the keywords can then be used to calculate points of interest upon that axis. For instance, in axes longer than 1, we have:

Minimum: CRVALn + CDELTn*(1-CRPIXn)

Center: CRVALn + CDELTn*(NAXISn/2 - CRPIXn)

Maximum: CRVALn + CDELTn*(NAXISn - CRPIXn)

For the Frequency axis, which only has a single point (NAXISn=1), our calculations are simpler:

Minimum: CRVALn - CDELTn/2

Center: CRVALn

Maximum: CRVALn +CDELTn/2

Image Sets Database Table:

The Image Set information will need to come from outside sources, as most of the information is not guaranteed to be in the FITS files themselves. Vlass Manager holds all the needed information for their images, but future development will need to provide the relevant metadata as image sources broaden beyond VLASS.

Column Name	VO Equivalent	Source	Comment
image_set_id obs_id		automatically generated	Unique Identifier for the Image Set
project_code		Required to facilitate Ingestion	
configuration		VlassMgr	This will need to hold the entire list used for the imaging.
collection_name	obs_collection	VlassMgr	
calibration_level	calib_level	VlassMgr	As defined by the VO in their 0-4 system
product_file_id		automatically generated	Link to the imaging products tar file
tags			internal tags which apply to all images of the set

VO ObsCore Remaining Fields:

VO Requirement	Value	Source
access_url		
access_estsize		files.filesize, or combined value for an image set
dataproduct_type	'image'	default
access_format	'fits'	default

obs_publisher_did		Obtained upon registering with the Virtual Observatory
facility_name	'NRAO'	default
t_resolution		images.exposure_time
t_xel	1	default
em_res_power	null	default
em_xel	1	default
pol_xel	1	default

Thumbnails

We won't store thumbnails in NGAS as such, for each we will:

- 1. compute the sha1 hash of the file
- store the file in a filesystem at \$ROOT/\$1/\$2/\$3/\$FILENAME, where \$ROOT is a CAPO property that maps to the root of the filesystem, \$1 is the first two characters of the sha1 sum, \$2 the second two, and \$3 the third two.
 in the metadata database we will store the \$1/\$2/\$3/\$FILENAME path